

FACTORY-DIRECT · OEM / ODM · EXPORT

Mini Skid Steer Loaders

Stand-On Wheeled & Tracked Compact Loaders

Compact stand-on skid steer loaders for landscaping, construction, farms and rental fleets. Narrow bodies pass through garden gates, while hydraulic quick-attach systems run buckets, augers, pallet forks, trenchers and more.



JSHY330

- B&S 13.5 HP gasoline
- 160 kg rated load · wheeled
- 1,040 mm narrow body



HY450

- RATO R740D 23 HP
- 200 kg rated load · tracked
- 2,380 mm lift height

Factory Direct

Source-factory pricing with volume tiers for dealers and rental fleets

OEM / ODM

Custom colors, private label, engine and attachment options

CE Certified

30-minute factory run-in test on every unit before shipment

Export Ready

20GP / 40HQ loading plans, mixed models in one container

Request a Quote & Container Loading Plan

Send your destination port, models, quantity and options. Our export team replies within 12 hours with factory-direct pricing, sea freight details, CE documentation and lead time.

EMAIL

info@hongtai-machine.com

WEBSITE

hongtai-machine.com

WHATSAPP / PHONE

+86 135 6279 5625

HOURS

Mon – Sat, 8:00 – 18:00 (UTC+8)

JSHY330

JSHY330 Stand-On Mini Skid Steer Loader (Briggs & Stratton 13.5 HP, Wheeled)



The HONGTAI JSHY330 stand-on mini skid steer loader packs real loader capability into a 1,040 mm (40.9 in) wide, 800 kg wheeled machine. The operator stands on the rear platform with a clear view of the bucket, steps off in seconds, and moves material through garden gates, side yards and tight job sites that a ride-on skid steer cannot reach.

KEY FEATURES

- Briggs & Stratton 13.5 HP gasoline engine, 3,200 rpm rated speed
- 160 kg rated load and 0.15 m³ standard bucket
- 2,375 mm lift height and 1,350 mm dump height
- 1,040 mm narrow body with 1,400 mm turning radius
- Dual-circuit hydraulic quick-attach system for fast tool changes
- Stand-on operation for good visibility and quick on-off

Technical Specifications

Parameter	Metric	Imperial
WEIGHT & CAPACITY		
Machine Weight	800 kg	1,764 lbs
Rated Load	160 kg	353 lbs
Bucket Capacity	0.15 m ³	5.3 ft ³
DIMENSIONS		
Overall Length (with bucket)	2,120 mm	83.5 in
Length without Bucket	1,738 mm	68.4 in
Overall Width	1,040 mm	40.9 in
Overall Height	1,290 mm	50.8 in
Wheelbase	640 mm	25.2 in
WORKING RANGE		
Max. Lift Height	2,375 mm	7.8 ft
Max. Hinge Pin Height	1,840 mm	6.0 ft
Max. Dump Height	1,350 mm	4.4 ft
Turning Radius	1,400 mm	4.6 ft
ENGINE & HYDRAULICS		
Engine	Briggs & Stratton gasoline engine	
Rated Power	13.5 HP	13.5 HP
Rated Speed	3,200 rpm	3,200 rpm
Hydraulic Pressure	17 MPa	2,466 psi
Hydraulic Oil Tank	26 L	6.9 US gal
Fuel Tank	6.6 L	1.7 US gal

Travel Speed

0 – 5 km/h

0 – 3.1 mph

CONFIGURATION

Standard

Bucket; dual-circuit hydraulic quick-attach system

TYPICAL APPLICATIONS

- Landscaping, garden construction and turf work
- Moving soil, gravel, mulch and building materials
- Site cleanup and backfilling on small construction jobs
- Farm, stable and nursery material handling
- Rental fleets serving homeowners and small contractors
- Tight-access work in backyards, alleys and inside buildings

STANDARD CONFIGURATION

- Briggs & Stratton 13.5 HP gasoline engine, standard bucket, dual-circuit hydraulic quick-attach system, 17 MPa hydraulic system with 26 L oil tank, wheeled chassis, stand-on operator platform.

ATTACHMENTS

- The dual-circuit hydraulic quick-attach system works with a range of mini loader tools such as pallet forks, augers, trenchers, grapples and leveling blades. Tell us which attachments you need and we will confirm what can be supplied and loaded in the same container.

HY450

HY450 Tracked Mini Skid Steer Loader (RATO R740D 23 HP)



The HONGTAI HY450 tracked mini skid steer loader is built for soft, muddy and uneven ground where wheels lose grip. Rubber tracks spread its 826 kg weight and keep it moving on wet lawns, sand and loose soil, while the 1,034 mm (40.7 in) body still fits through standard gates and narrow site access.

KEY FEATURES

- RATO R740D 23 HP gasoline engine, 3,200 rpm rated speed
- 200 kg rated load and 0.17 m³ standard bucket
- Rubber track undercarriage with 110 mm ground clearance
- 2,380 mm lift height and 1,855 mm hinge pin height
- 21 L fuel tank for long working shifts
- Dual-circuit hydraulic quick-attach system for fast tool changes

Technical Specifications

Parameter	Metric	Imperial
WEIGHT & CAPACITY		
Machine Weight	826 kg	1,821 lbs
Rated Load	200 kg	441 lbs
Bucket Capacity	0.17 m ³	6.0 ft ³
DIMENSIONS		
Overall Length (with bucket)	2,350 mm	92.5 in
Length without Bucket	1,790 mm	70.5 in
Overall Width	1,034 mm	40.7 in
Overall Height	1,260 mm	49.6 in
Ground Clearance	110 mm	4.3 in
WORKING RANGE		
Max. Lift Height	2,380 mm	7.8 ft
Max. Hinge Pin Height	1,855 mm	6.1 ft
Dump Height	1,317 mm	4.3 ft
Turning Radius	1,317 mm	4.3 ft
ENGINE & HYDRAULICS		
Engine	RATO R740D gasoline engine	
Rated Power	23 HP	23 HP
Rated Speed	3,200 rpm	3,200 rpm
Hydraulic Pressure	17 MPa	2,466 psi
Hydraulic Oil Tank	26 L	6.9 US gal
Fuel Tank	21 L	5.5 US gal

Travel Speed

0 – 5 km/h

0 – 3.1 mph

CONFIGURATION

Standard

Bucket; dual-circuit hydraulic quick-attach system

TYPICAL APPLICATIONS

- Landscaping, garden construction and turf work
- Moving soil, gravel, mulch and building materials
- Site cleanup and backfilling on small construction jobs
- Farm, stable and nursery material handling
- Rental fleets serving homeowners and small contractors
- Tight-access work in backyards, alleys and inside buildings

STANDARD CONFIGURATION

- RATO R740D 23 HP gasoline engine, standard bucket, dual-circuit hydraulic quick-attach system, 17 MPa hydraulic system with 26 L oil tank, rubber track undercarriage.

ATTACHMENTS

- The dual-circuit hydraulic quick-attach system works with a range of mini loader tools such as pallet forks, augers, trenchers, grapples and leveling blades. Tell us which attachments you need and we will confirm what can be supplied and loaded in the same container.

Specifications are for reference and may change with product improvements without notice. Please confirm the final configuration with our sales team before ordering. © 2026 HONGTAI Machinery.