

FACTORY-DIRECT · OEM / ODM · EXPORT

Mini Tracked Dumpers

High-Lift, Rotary & Self-Loading Crawler Dumpers

Rubber-track mini dumpers that carry 500 – 1,000 kg through narrow access and soft ground. Choose scissor high-lift tipping, a 180° rotary tipper or a self-loading one-ton model for building sites, landscaping and farms.



HT-500L

- 500 kg · scissor lift to 1,400 mm
- B&S XR950 6.5 HP
- 700 mm wide tracks



HT-500R

- 500 kg · 180° rotary tipper
- Self-loading shovel
- B&S XR950 6.5 HP



HT-1000L

- 1,000 kg transport load
- Self-loading + lift tipper
- RATO R500 19.5 HP

Factory Direct

Source-factory pricing with volume tiers for dealers and rental fleets

OEM / ODM

Custom colors, private label, engine and attachment options

CE Certified

30-minute factory run-in test on every unit before shipment

Export Ready

20GP / 40HQ loading plans, mixed models in one container

Request a Quote & Container Loading Plan

Send your destination port, models, quantity and options. Our export team replies within 12 hours with factory-direct pricing, sea freight details, CE documentation and lead time.

EMAIL
info@hongtai-machine.com

WEBSITE
hongtai-machine.com

WHATSAPP / PHONE
[+86 135 6279 5625](https://api.whatsapp.com/message/62795625)

HOURS
Mon – Sat, 8:00 – 18:00 (UTC+8)

HT-500L

HT-500L High Lift Tracked Dumper (Scissor Lift, 500 kg, B&S 6.5 HP)



The HONGTAI HT-500L high lift tracked dumper carries up to 500 kg across soft or uneven ground and then raises its 200 L load box on a scissor lift to 1,400 mm. That lets the operator tip straight into skips, trailers, mixers and raised beds instead of shoveling material a second time.

KEY FEATURES

- Scissor-lift tipper raises the 200 L load box to 1,400 mm
- 500 kg maximum load
- Briggs & Stratton XR950 208 cc gasoline engine, 6.5 HP
- Hydraulic tipping with 100° tipping angle
- 700 mm wide rubber-track chassis, 490 kg
- 1.15 m turning radius for tight sites

Technical Specifications

Parameter	Metric	Imperial
LOAD & TIPPING		
Maximum Load	500 kg	1,102 lbs
Load Box Capacity	200 L	7.1 ft ³
Load Box Size	1,050 × 730 × 730 mm	41.3 × 28.7 × 28.7 in
Lifting Height	1,400 mm	55.1 in
Tipping	Hydraulic, scissor-lift tipper	
Tipping Angle	100°	100°
Rotation Angle	180°	180°
DIMENSIONS & WEIGHT		
Machine Weight	490 kg	1,080 lbs
Overall Size (L × W × H)	1,570 × 880 × 2,300 mm	61.8 × 34.6 × 90.6 in
UNDERCARRIAGE & TRAVEL		
Chassis Width	700 mm	27.6 in
Track Width	180 mm	7.1 in
Track Ground Contact Length	1,000 mm	39.4 in
Track Center Distance	520 mm	20.5 in
Ground Clearance	110 mm	4.3 in
Travel Speed	2.88 km/h	1.8 mph
Min. Turning Radius	1.15 m	3.8 ft
ENGINE & HYDRAULICS		
Engine	Briggs & Stratton XR950, single-cylinder, four-stroke, air-cooled gasoline	
Displacement	208 cc	12.7 in ³

Rated Power	6.5 HP / 3,600 rpm	6.5 HP
Fuel	Unleaded gasoline (RON 92)	
Fuel Consumption	≤ 395 g/kWh	—
Fuel Tank	3.1 L	0.8 US gal
Engine Oil	0.6 L	0.6 US qt
Hydraulic Oil	ISO VG 46 anti-wear	
Hydraulic Oil Tank	15 L	4.0 US gal

TYPICAL APPLICATIONS

- Moving soil, gravel, sand and rubble on building and landscaping sites
- Carrying bricks, blocks, paving and building materials through narrow access
- Backyard excavation and spoil removal behind homes and terraces
- Loading skips and containers with the raised or rotating tipper
- Farm, orchard, nursery and stable material handling
- Rental fleets serving builders, landscapers and homeowners

HT-500R

HT-500R Rotary Tracked Dumper (180° Swivel, Self-Loading, 500 kg, B&S 6.5 HP)



The HONGTAI HT-500R rotary tracked dumper combines a self-loading shovel with a load box that swivels through 180°. The operator fills the 200 L box from the material pile, drives to the work area and tips to the front or to either side, without having to turn the machine around in tight spaces.

KEY FEATURES

- 180° rotating tipper for dumping to the front or either side
- Self-loading shovel fills the 200 L load box without extra labor
- 500 kg maximum load
- Briggs & Stratton XR950 208 cc gasoline engine, 6.5 HP
- 700 mm wide rubber-track chassis, 500 kg
- Hydraulic tipping with 100° tipping angle

Technical Specifications

Parameter	Metric	Imperial
LOAD & TIPPING		
Maximum Load	500 kg	1,102 lbs
Load Box Capacity	200 L	7.1 ft ³
Load Box Size	1,050 × 730 × 730 mm	41.3 × 28.7 × 28.7 in
Tipping	Hydraulic tipper	
Tipping Angle	100°	100°
Rotation Angle	180°	180°
DIMENSIONS & WEIGHT		
Machine Weight	500 kg	1,102 lbs
Overall Size (without pedal & shovel)	1,570 × 880 × 1,300 mm	61.8 × 34.6 × 51.2 in
Overall Size (with pedal & shovel)	2,050 × 880 × 1,300 mm	80.7 × 34.6 × 51.2 in
UNDERCARRIAGE & TRAVEL		
Chassis Width	700 mm	27.6 in
Track Width	180 mm	7.1 in
Track Ground Contact Length	1,000 mm	39.4 in
Track Center Distance	520 mm	20.5 in
Ground Clearance	110 mm	4.3 in
Travel Speed	2.88 km/h	1.8 mph
Min. Turning Radius	1.15 m	3.8 ft
ENGINE & HYDRAULICS		
Engine	Briggs & Stratton XR950, single-cylinder, four-stroke, air-cooled gasoline	
Displacement	208 cc	12.7 in ³

Rated Power	6.5 HP / 3,600 rpm	6.5 HP
Fuel	Unleaded gasoline (RON 92)	
Fuel Consumption	≤ 395 g/kWh	—
Fuel Tank	3.1 L	0.8 US gal
Engine Oil	0.6 L	0.6 US qt
Hydraulic Oil	ISO VG 46 anti-wear	
Hydraulic Oil Tank	15 L	4.0 US gal

TYPICAL APPLICATIONS

- Moving soil, gravel, sand and rubble on building and landscaping sites
- Carrying bricks, blocks, paving and building materials through narrow access
- Backyard excavation and spoil removal behind homes and terraces
- Loading skips and containers with the raised or rotating tipper
- Farm, orchard, nursery and stable material handling
- Rental fleets serving builders, landscapers and homeowners

HT-1000L

HT-1000L Self-Loading Lift Tracked Dumper (1,000 kg, RATO R500 19.5 HP)



The HONGTAI HT-1000L self-loading lift tracked dumper is the heavy-duty model in our range. It carries up to 1,000 kg in its 1,450 × 650 × 400 mm container, fills itself with a front loading bucket, and raises loads of up to 800 kg on its hydraulic lift tipper to empty into skips, trailers and hoppers.

KEY FEATURES

- 1,000 kg transport load and 800 kg maximum lifting capacity
- Self-loading front bucket and hydraulic lift tipper
- RATO R500 500 cc gasoline engine, 19.5 HP / 11 kW
- 1,450 × 650 × 400 mm load container
- 700 mm wide rubber tracks with 1,200 mm ground contact
- 20 L hydraulic tank and 6.9 L fuel tank

Technical Specifications

Parameter	Metric	Imperial
LOAD & TIPPING		
Max. Transport Load (horizontal)	1,000 kg	2,205 lbs
Max. Lifting Capacity	800 kg	1,764 lbs
Container Size	1,450 × 650 × 400 mm	57.1 × 25.6 × 15.7 in
Loading Bucket Size	700 × 800 × 220 mm	27.6 × 31.5 × 8.7 in
Dumping	Hydraulic lift bucket	
Dumping Angle	100°	100°
DIMENSIONS & WEIGHT		
Machine Weight	690 kg	1,521 lbs
Overall Size (with pedal & bucket)	2,000 × 900 × 2,000 mm	78.7 × 35.4 × 78.7 in
UNDERCARRIAGE		
Chassis Width	700 mm	27.6 in
Track Width	180 mm	7.1 in
Track Ground Contact Length	1,200 mm	47.2 in
Ground Clearance	110 mm	4.3 in
ENGINE & HYDRAULICS		
Engine	RATO R500, single-cylinder, four-stroke gasoline	
Displacement	500 cc	30.5 in ³
Rated Power	11 kW / 3,600 rpm	19.5 HP
Fuel	Unleaded gasoline (RON 92)	
Fuel Tank	6.9 L	1.8 US gal
Engine Oil	1.2 L	1.3 US qt

Hydraulic Oil	ISO VG 46 anti-wear	
Hydraulic Oil Tank	20 L	5.3 US gal

TYPICAL APPLICATIONS

- Moving soil, gravel, sand and rubble on building and landscaping sites
 - Carrying bricks, blocks, paving and building materials through narrow access
 - Backyard excavation and spoil removal behind homes and terraces
- Loading skips and containers with the raised or rotating tipper
 - Farm, orchard, nursery and stable material handling
 - Rental fleets serving builders, landscapers and homeowners

Specifications are for reference and may change with product improvements without notice. Please confirm the final configuration with our sales team before ordering. © 2026 HONGTAI Machinery.